

EL 515 Plus Set Fully automatic rotating laser


Aligned to your needs.

Ready to use and fully equipped for many applications: Either the elevating tripod or the wall mount can be used, depending on the situation. Target plate and laser glasses for improved visibility of the laser beam. Receiver and handy levelling staff for determining height differences. With rechargeable battery and charger, and the option of operating the device with alkaline batteries.



Technical Data

Self-levelling range	± 3°
Accuracy	± 1,5 mm / 10 m
Working range without receiver Ø	30 m*
Working range with receiver Ø	400 m
Rotating speed (rpm)	200, 400, 600
Power supply	NiMH
Operating time	20 h
Dust/water protection	IP 54
Laser diode / class	635 nm / 2
Temperature range	-10°C to +45°C
Weight (instrument with battery)	1,5 kg



Features

- Instant self-levelling
- Horizontal self-levelling rotating laser; vertical levelling with one footscrew
- Automatic shut-off and audible alarm when out of self-levelling range
- Variable rotating speed
- Permanent 90° beam to zenith
- Rechargeable NiMH batteries with intelligent charger
- Integrated floor/wall mount with adjustment screw

Supplied with

- Receiver EL 702 with clamp for levelling staff
- NiMH batteries and intelligent charger
- Height adjustable wallmount with adjustable range of 21 cm
- Lightweight elevating tripod, working range 0,55 1,58 m
- Telescopic levelling staff, 5 sections, working range 0,67 2,45 m
- Magnetic target
- Laser intensive glasses

Page 1/1 geo-FENNEL GmbH

- Hard case