

mase
GENERATORS



MPL 22 SS-Y/MV

mase
GENERATORS

MASE GENERATORS S.p.A.

Via Tortona, 345 - 47522 Cesena (FC) Italy
Tel. (+39) 0547-354311 - Fax (+39) 0547-354311
E-mail: commercial@masegenerators.com
www.masegenerators.com

MPL 22 SS-Y/MV

SUPER SILENCED Single-phase POWER GENERATOR / OUTPUT POWER 22 KVA
DIESEL ENGINE 1500 RPM

Gen Set Features	<ul style="list-style-type: none"> + Controller (DSE 3110) with digital display for full monitoring of generator parameters: generator voltage, generator frequency, battery voltage, hour meter; with auto engine protection shutdown system in case of: <ul style="list-style-type: none"> - low oil pressure - high coolant temperature - low fuel level - over voltage - over frequency - under frequency + 12 V built-in battery with electric start + Water temperature gauge + Oil pressure gauge + Fuel level gauge + Battery switch + Emergency STOP button 	<ul style="list-style-type: none"> + Remote control terminal board + Earth Leakage Circuit Breaker (ELCB) + Main circuit breakers + 110 / 230 V selector switch + 2x32A, 230V - 50Hz single-phase EEC sockets protected by circuit breakers + 2x16A, 230V - 50Hz single-phase EEC sockets protected by circuit breakers + 3x32A, 110V - 50Hz single-phase EEC sockets protected by circuit breakers + 1x16A, 110V - 50Hz single-phase EEC socket protected by circuit breaker + Hard wire facility - 230 / 110 V + Separate tank facility c/w quick release couplings + Central lifting eye + Fork-lift pockets
Gen Set Options (available as factory options)	<ul style="list-style-type: none"> + Version with AMF/ATS function + Engine water heaters powered by mains 230 V - 50 Hz 	
Accessories on Request	<ul style="list-style-type: none"> + Remote Start/Stop kit by cable (20 m) 	
Noise Level	<ul style="list-style-type: none"> + Lwa 89 (64 dB a 7 m) 	
AC Generator 50 Hz	<ul style="list-style-type: none"> + Type: synchronous + Single-phase power: 22 kVA - 230 V + Single-phase power: 22 kVA - 110 V (C.T.E.) + Power Factor: $\cos \phi$ 0,8 	
Diesel Engine 1500 rpm	<ul style="list-style-type: none"> + Type: Yanmar 4TNV-88 - 4 cyl. 24,1 HP (18 kWm) - 2189 cm³ + Fuel: diesel + Cooling system: water + Starting system: electric + Fuel tank capacity: 135 l + Fuel consumption @ 75%: 3,9 l/h 	
Other Features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 mt (*) + Mechanical Protection: IP 23 + Dimensions (L x W x H): 1821 x 819 x 1310 mm + Dry weight: 729 kg + Total weight: 843 kg 	

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of costumer program, we reserve the right to change data without notice.