

**mase**  
**GENERATORS**

 **GenSet**



**MW 8/300 I-K**

**CE**

**MASE GENERATORS S.p.A.**  
Via Tortona,345 - 47522 Cesena (FC) Italy  
Tel. (+39) 0547-354311 - Fax (+39) 0547-354311  
E-mail: [commercial@masegenerators.com](mailto:commercial@masegenerators.com)

**ENGINE DRIVEN WELDER/GENERATOR - WELDING OUTPUT POWER 300A DC  
THREE-PHASE AND SINGLE-PHASE AUXILIARY POWER AVAILABLE  
DIESEL ENGINE 3000 RPM**

<b>Standard Features</b>	<b>Processes: SMAW (stick) / Tig</b> <ul style="list-style-type: none"> <li>• Controller (DSE 3110) with digital display for full monitoring of generator parameters: generator voltage, battery voltage, frequency, hour meter; with auto engine protection shutdown system in case of: <ul style="list-style-type: none"> <li>- fail to start</li> <li>- low oil pressure</li> <li>- low fuel level</li> <li>- high coolant temperature</li> <li>- over/under voltage</li> <li>- over/under frequency</li> </ul> </li> <li>• Fuel level gauge</li> </ul>	<ul style="list-style-type: none"> <li>• 1 x 16 A, 400 V three-phase EEC socket</li> <li>• 1 x 32 A, 230 V single-phase EEC socket protected by circuit breaker</li> <li>• Earth Leakage Circuit Breaker</li> <li>• Remote control socket</li> <li>• ARC FORCE CONTROL switch</li> <li>• Automatic idle device when no load is connected</li> <li>• 12V built-in battery with electric start</li> <li>• Central lifting eye</li> </ul>
<b>Options available</b>	<ul style="list-style-type: none"> <li>• LIFT START TIG facility</li> <li>• CC/CV control for MIG welding</li> <li>• Spark arrester muffler</li> <li>• Emergency stop button</li> </ul>	<ul style="list-style-type: none"> <li>• Version with different voltages</li> <li>• 60 Hz version</li> <li>• 48 V 50 Hz single-phase output</li> </ul>
<b>Accessories on request</b>	<ul style="list-style-type: none"> <li>• Trolley: two-wheels and handles</li> <li>• Two-wheels site tow undercarriage (GRT2W)</li> <li>• Remote control unit with 20 m cable and plug</li> <li>• Parallel Welding Box with ammeter and voltmeter (P-BOX)</li> </ul>	<ul style="list-style-type: none"> <li>• Welding cables Ø 35 mm<sup>2</sup> (5+3 m) with accessories</li> <li>• Reverse polarity switch kit</li> <li>• MIG wire feeder</li> </ul>
<b>Noise level</b>	<ul style="list-style-type: none"> <li>• Lwa 99 (74 dB at 7 mt)</li> </ul>	
<b>DC welding</b>	<ul style="list-style-type: none"> <li>• Duty Cycle @ 35%: 300 A - 32 V</li> <li>• Duty Cycle @ 60%: 270 A - 31 V</li> <li>• Stepless current control: 30 A - 300 A</li> <li>• Open Circuit Voltage: 70 V</li> <li>• Max welding rod: 6 mm</li> </ul>	
<b>AC generator - 50Hz</b>	<ul style="list-style-type: none"> <li>• Type: asynchronous self-excited and self-protected</li> <li>• Three-phase power: 8 kVA - 400 V</li> <li>• Single-phase power: 7 kVA - 230 V</li> <li>• Power Factor: cos φ 0,8</li> </ul>	
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"> <li>• Type: Kubota D722 - 3 cyl. - 719 cm<sup>3</sup></li> <li>• Max power: 19 hp (14 kWm)</li> <li>• Starting system: electric (12Vdc)</li> <li>• Cooling system: water</li> <li>• Fuel consumption @ 75%: 3,3 lt/h</li> </ul>	
<b>Other features</b>	<ul style="list-style-type: none"> <li>• Insulation Class: H</li> <li>• Ambient temperature: 40 °C (*)</li> <li>• Altitude: 1000 m (*)</li> <li>• Mechanical Protection: IP 23</li> <li>• Fuel tank capacity: 30 lt</li> <li>• Dimensions (L x W x H): 1360 x 530 x 870 mm</li> <li>• Dry weight: 345 kg</li> </ul>	

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.