



HYDRAULIC

TROLLEY JACKS



T2X and T1.5H models allows for excellent manoeuvrability.

A-5182
50 mm extension. **Optional**

A-5181 Rubber pad for the saddle. **Optional**



Easily accessible thanks to a very low chassis on 2-ton models (135 mm at their highest point).

75 mm at the highest point of elevation on the T2.

Extra-low point of elevation and extended access platform (48 mm without saddle) on the T2X model, providing exceptional accessibility.

T2



A-5175
Only for T2 y T1.5H. **Optional**

The TJ models maintain their known technical characteristics until their forthcoming adaptation to the design marked by the T models.

T2X



Capacity (t)	2	1,5	2	2	3	6	10	12	15	20
A	120	110	75	48	140	195	195	195	180	205
B	370	665	390	455	385	380	380	380	395	380
C	165	165	135	135	185	220	260	260	255	300
D	490	775	465	520	525	575	575	575	575	585
E	590	1250	880	920	1150	1300	1600	1600	1845	1845
F	1255	2180	1810	1850	2080	2300	2600	2600	2845	2845
G	345	360	360	360	360	425	425	425	360	410
H	275	360	260	260	260	300	345	350	220	270
Weight (kg)	30	60.5	32	43	50	82	111.5	130.5	160	257
References	TJE-2	T1,5H	T2	T2X	T3	TJ-6A	TJ-10A	TJ-12A	TJ-15A	TJ-20A