

**SAFETY DATA SHEET**  
according to 1907/2006/EC, Article 31

Page 1/7

**GALVANISING SPRAY AEROSOL**

Revision 4  
Revision date 2023-04-03

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Product name	GALVANISING SPRAY AEROSOL
--------------	---------------------------

1.3. Details of the supplier of the safety data sheet

Company	STEVENS INDUSTRIAL SERVICES (SIS) LTD
Address	Unit 7 Hatfield Way South Church Enterprise Park Bishop Auckland DL14 6XF
Web	www.stevens-sis.co.uk
Telephone	01388 772233
Fax	01388 772263
Email	sales@stevens-sis.co.uk
Email address of the competent person	sales@stevens-sis.co.uk

1.4. Emergency telephone number


Emergency telephone number	01388 772233 Mon - Fri 9.00 am - 5.00pm
----------------------------	--

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	F+; R12 Xi; R36 R66-67 Symbols: F+: Extremely flammable. Xi: Irritant.
Main hazards	Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 1: H224; Eye Irrit. 2: H319; STOT SE 3: H336;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 1: H224 - Extremely flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed.

# GALVANISING SPRAY AEROSOL

Revision 4  
Revision date 2023-04-23

## 2.2. Label elements

Precautionary Statement: Response	<p>P240 - Ground/bond container and receiving equipment.  P241 - Use explosion-proof electrical/ventilating/lighting/equipment.  P242 - Use only non-sparking tools.  P243 - Take precautionary measures against static discharge.  P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  P264 - Wash thoroughly after handling.  P271 - Use only outdoors or in a well-ventilated area.  P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P312 - Call a POISON CENTER/doctor/ if you feel unwell.  P337+P313 - If eye irritation persists: Get medical advice/attention.  P370+P378 - In case of fire: Use to extinguish.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  P403+P235 - Store in a well-ventilated place. Keep cool.  P405 - Store locked up.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to</p>

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Acetone	606-001-00-8	67-64-1	200-662-2		50 - 60%	F; R11 Xi; R36 R66 R67	
Butane	601-004-00-0	106-97-8	203-448-7		10 - 20%	F+; R12	
o-Xylene	601-022-00-9	95-47-6	202-422-2		1 - 10%	R10 Xn; R20/21 Xi; R38	
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	607-195-00-7	108-65-6	203-603-9		0 - 0.5%	R10	
Ethylbenzene	601-023-00-4	100-41-4	202-849-4		0 - 0.5%	F; R11 Xn; R20	
Toluene	601-021-00-3	108-88-3	203-625-9		0 - 0.5%	F; R11 Repr. Cat. 3; R63 Xn; R48/20-65 Xi; R38 R67	
Cumene	601-024-00-X	98-82-8	202-704-5		0 - 0.5%	R10 Xn; R65 Xi; R37 N; R51/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Acetone	606-001-00-8	67-64-1	200-662-2		50 - 60%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
Butane	601-004-00-0	106-97-8	203-448-7		10 - 20%	Flam. Gas 1: H220;	
o-Xylene	601-022-00-9	95-47-6	202-422-2		1 - 10%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;	

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation may cause nausea and vomiting. May cause dizziness and headache. May cause irritation to mucous membranes. Seek medical attention if irritation or symptoms persist.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the

# GALVANISING SPRAY AEROSOL

Revision 4  
Revision date 2023-04-03

## 4.1. Description of first aid measures

Skin contact	eyelids open. Seek medical attention if irritation or symptoms persist. May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

## General information

	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
--	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Carbon oxides. Alcohol resistant foam.
--	--

### 5.2. Special hazards arising from the substance or mixture

	Vapour may travel considerable distance to source of ignition and flash back.
--	---

### 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Avoid contact with: Sources of heat and direct sunlight. Keep in a cool, dry, well ventilated area. Keep out of the reach of children. Store at temperatures below 40 °C.
--	--

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Exposure Limit Values

# GALVANISING SPRAY AEROSOL

Revision 4

Revision date 2023-04-03

## 8.1.1. Exposure Limit Values

2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50  WEL 15 min limit ppm: 100 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 274  WEL 15 min limit mg/m3: 548 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Acetone	WEL 8-hr limit ppm: 500 WEL 15 min limit ppm: 1500 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 1210 WEL 15 min limit mg/m3: 3620 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Butane	WEL 8-hr limit ppm: 600 WEL 15 min limit ppm: 750 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 1450 WEL 15 min limit mg/m3: 1810 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Cumene	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Ethylbenzene	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 125 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 441 WEL 15 min limit mg/m3: 552 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
o-Xylene	DIR: 2000/39 8hTWA mg/m3: 221 STEL mg/m3: 442	8hTWA ppm: 50 STEL ppm: 100 NOT: Skin
Toluene	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 8-hr limit mg/m3: 191 WEL 15 min limit mg/m3: 384 WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Hand protection	Chemical resistant gloves (PVC).
Respiratory protection	Wear suitable respiratory equipment when necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

# GALVANISING SPRAY AEROSOL

Revision 4

Revision date 2023-04-03

## 9.1. Information on basic physical and chemical properties

Appearance	= Aerosol
Colour	= Silver
Odour	= Aromatic
Initial boiling point	-40
Flash point	-40
Solubility	=

### Water solubility

	Insoluble in water.
--	---------------------

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

### 10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

### 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

	INHALATION: May cause drowsiness or dizziness.
--	--

#### 11.1.4. Toxicological Information

	No data is available on this product.
--	---------------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

	No data is available on this product.
--	---------------------------------------

## SECTION 13: Disposal considerations

### General information

	Dispose of in compliance with all local and national regulations.
--	---

### Disposal methods

	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
--	---

### Disposal of packaging

	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.
--	--

## SECTION 14: Transport information

### Hazard pictograms

	
--	---

#### 14.1. UN number

	UN1950
--	--------

#### 14.2. UN proper shipping name

--	--

## GALVANISING SPRAY AEROSOL

Revision 4

Revision date 2023-04-23

## 14.2. UN proper shipping name

AEROSOLS

## 14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

## 14.4. Packing group

Packing group -

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	-
Tunnel Category	(D)

## IMDG

EmS Code	F-D S-U
----------	---------

## IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

## SECTION 15: Regulatory information

## SECTION 16: Other information

## Other information

Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> <li>2 - 2.1. Classification of the substance or mixture.</li> <li>2 - 2.1.2. Classification - EC 1272/2008.</li> <li>2 - Hazard pictograms.</li> <li>2 - Signal Word.</li> <li>2 - Precautionary Statement: Prevention.</li> <li>2 - Precautionary Statement: Response.</li> <li>2 - Precautionary Statement: Storage.</li> <li>2 - Precautionary Statement: Disposal.</li> <li>9 - 9.1. Information on basic physical and chemical properties (Appearance).</li> <li>9 - 9.1. Information on basic physical and chemical properties (Colour).</li> <li>9 - 9.1. Information on basic physical and chemical properties (Odour).</li> <li>9 - 9.1. Information on basic physical and chemical properties (Solubility).</li> <li>11 - 11.1. Information on toxicological effects.</li> <li>12 - 12.1. Toxicity.</li> <li>15 - Labelling.</li> <li>15 - Risk phrases.</li> </ul>
----------	--

# GALVANISING SPRAY AEROSOL

Revision 4

Revision date 2023-04-23

## Other information

Text of risk phrases in Section 3	<p>R10 - Flammable  R11 - Highly flammable.  R12 - Extremely flammable.  R20/21 - Harmful by inhalation and in contact with skin.  R20 - Harmful by inhalation.  R36 - Irritating to eyes.  R37 - Irritating to respiratory system.  R38 - Irritating to skin.  R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.  R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  R63 - Possible risk of harm to the unborn child.  R65 - Harmful: may cause lung damage if swallowed.  R66 - Repeated exposure may cause skin dryness or cracking.  R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>EUH066 - Repeated exposure may cause skin dryness or cracking.  Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  Eye Irrit. 2: H319 - Causes serious eye irritation.  STOT SE 3: H336 - May cause drowsiness or dizziness.  Flam. Gas 1: H220 - Extremely flammable gas.  Flam. Liq. 3: H226 - Flammable liquid and vapour.  Acute Tox. 4: H312 - Harmful in contact with skin.  Skin Irrit. 2: H315 - Causes skin irritation.  Acute Tox. 4: H332 - Harmful if inhaled.</p>

## Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---